

NewAge Petro Conchem  
Pvt. Ltd.

# Product Specification Sheet

**Automatic Transmission Fluid (ATF)**



Reliable quality, trusted performance

## AUTOMATIC TRANSMISSION FLUID

Automatic Transmission Fluid (ATF) is a high-performance lubricant specially formulated for automatic transmissions. It ensures smooth gear shifting, excellent thermal stability, wear protection, and extended transmission life under demanding operating conditions.

Available Grades:

- ATF Type A
- ATF Dextron III
- ATF Dextron VI

Analytical Test	Typical Specification		
	ATF Type A	ATF Dextron III	ATF Dextron VI
Color By Gardner	< 3.0	< 3.0	< 3.0
Appearance	Clear & Bright	Clear & Bright	Clear & Bright
Density @ 29.5 °C	0.830 – 0.860	0.830 – 0.860	0.830 – 860
K. Viscosity @40 °C	To Report	To Report	To Report
K. Viscosity @ 100 °C	7.00 to 8.50	40 to 50	6 to 8
Viscosity Index	Min 110	Min 140	Min 140
Flash Point, COC	Min 190°C	Min 200°C	Min 200°C
Pour Point	Max -18°C	Max -30°C	Max -33°C

### Advantages :

- Smooth & Seamless Gear Shifting
- High Thermal & Oxidation Stability
- Superior Wear Protection
- Excellent Friction Control
- Improved Fuel Efficiency
- Extended Drain Intervals
- Outstanding Low-Temperature Flow
- High Flash Point for Safety
- Enhanced Transmission Durability